

HEAVY-DUTY HYDRAULIC STABILIZATION LEGS



Power, performance and reliability for the toughest applications

Safely support and level a wide range of the most rugged equipment in the toughest work environments. Our heavy-duty stabilization legs arrive completely assembled and tested with a bolt-on, outer tube mount conveniently integrated into the design.

HEAVY-DUTY LEG OVERVIEW FOR UP TO 85,000LB LEG CAPACITY

LARGER CAPACITY

Heavy-duty stabilization legs offer greater lift capacity and mechanical load holding. Depending on the stroke size HD Stabilization legs offer 10 to 20% additional side load capacity.

RUGGED ALL-WEATHER DESIGN

Designed to withstand all temperatures, including extreme cold, heavy-duty legs have a dual cylinder guide ring to help keep external contaminants out and offer lateral stability. The durable locknut construction also provides solid support.

ENHANCED PRODUCTIVITY

The flexible design allows you to optimize your in-house processes. The legs are shipped complete, with no assembly process required.

IMPROVED SAFETY

Integrated dual counterbalance valves eliminate potential catastrophic failures when the valve is remotely located. The relieving function ensures the heavy-duty legs have positive load holding in case of pressure loss.



HEAVY-DUTY HYDRAULIC STABILIZATION LEGS

Our Heavy-Duty Hydraulic Stabilization Leg product line offers several options:

- 5- and 6-inch bore options
- 12-, 18-, 24- and 36-inch stroke options
- 58,000 to 85,000-pound leg capacity
- 170,000-pound mechanical load holding
- 0 to 20% side-load capacity
- 14- and 20-degree swivel shoe options
- 11- and 25.5-inch mounting plate option
- 5 gpm maximum flow rate

Why Choose Power-Packer Heavy-Duty Stabilization Legs



HEAVY-DUTY STABILIZATION LEGS

| Heavy-Duty Stabilization Leg | | | | | | | | | | | | | | | |
|------------------------------|------------------|------|-----|--------|-----|-------------------------|-------|----------------------|-----|-------------------|-----|---------------|-----|--------|--------|
| Part Number | Mech. Locking | Bore | | Stroke | | Mounting Height (MH) | | Bracket Width (W) | | Bracket Height | | Hole Width | | Weight | |
| | | in. | mm | in. | mm | in. | mm | in. | mm | in. | mm | in. | mm | lbs. | kg |
| 9010001341 | Yes | 5.0 | 127 | 12.0 | 305 | 18.65 | 473.7 | 12.0 | 305 | 11.0 | 279 | 10.0 | 254 | 240 | 108.86 |
| 9010001347 | Yes | 5.0 | 127 | 18.0 | 457 | 34.65 | 880.1 | 12.0 | 305 | 25.5 | 648 | 10.0 | 254 | 320 | 145.15 |
| 9010001345 | Yes | 5.0 | 127 | 24.0 | 610 | 34.65 | 880.1 | 12.0 | 305 | 25.5 | 648 | 10.0 | 254 | 375 | 170.10 |
| 9010001346 | Yes | 5.0 | 127 | 36.0 | 914 | 34.65 | 880.1 | 12.0 | 305 | 25.5 | 648 | 10.0 | 254 | 420 | 190.51 |
| 9010001290 | Yes | 6.0 | 152 | 12.0 | 305 | 18.65 | 473.7 | 12.0 | 305 | 11.0 | 279 | 10.0 | 254 | 280 | 127.01 |
| 9010001292 | Yes | 6.0 | 152 | 18.0 | 457 | 34.65 | 880.1 | 12.0 | 305 | 25.5 | 648 | 10.0 | 254 | 370 | 167.83 |
| 9010001293 | Yes | 6.0 | 152 | 24.0 | 610 | 34.65 | 880.1 | 12.0 | 305 | 25.5 | 648 | 10.0 | 254 | 430 | 195.04 |
| 9010001294 | Yes | 6.0 | 152 | 36.0 | 914 | 34.65 | 880.1 | 12.0 | 305 | 25.5 | 648 | 10.0 | 254 | 480 | 217.72 |

